

## MATERIAL TESTING LABORATORY Page No: 101 MILITARY ENGINEER SERVICES (MES) Copy no: 02 TEST RESULT FOR FINENESS MODULUS(F.M.) OF SAND.

Job No : 82/2024-2025(Sand). Name of Clint : GE (Army) Rangpur.

Ref ltr no : EinC/112 of 2024-2025/06/E-6 Dt.14 May'2025
Project Name : Construction of 1x Gate with Sentry Box.

Sample Specimen : Local Sand
Dt of sample collection :17 May'2025

Test Standard : ASTM/BS

Sieve Size	Wt of Material	Percentage Matarial	Cumulative % Retained	%Finer	Remarks
	Retainned(gms)	Retained(Round)			
# 4	0.94	0.24	0.24		
#8	3.28	0.82	1.06		
#16	18.28	4.57	5.63		
# 30	101.02	25.26	30.88		
# 50	190.66	47.67	78.55		FM= 2.15
#100	81.65	20.41	98.96		
# 200	3.32	0.83			
#Pan	0.74	0.19			
			Σ= 215.30		

## Cautions:

- 1 Samples as supplied to the laboratory have been tested. The laboratory authority does not bear any responsibility as to the representative character of the sample to be tested.
- 2 It is recommended that samples are sent in a sealed cover/packet/container under signature of the competent authority
- 3 In oder to be avoid fraudulent fabrication of the test result, it is recommended that test reports should be collected by duly authorized person and not by the contractor/supplier.

## Observation on Specimen(if any):

1

<u>Laboratory Technician</u> <u>Test Performed By</u> <u>Vetted By</u>

## Permissable Value:

1.For Sylhet/Domar sand minimum FM will be = 2.50

2.For Local sand minimum FM will be = 1.5

3.For Vitty sand minimum FM will be = 0.80